

FILM HANDING MACHINE

胶膜整理机

功能描述

- 自动纠正一道胶膜和玻璃铺设偏差。
- 实现胶膜刮平和点烫定位功能。
- 玻璃伺服归正，不同版型组件一键式切换。

Features

- Automatic correction of 1st adhesive film and glass laying deviation.
- Realize the functions of film scraping and hot spot positioning.
- Glass servo alignment, one-click switching of different modules.



设备技术性能

通过视觉和伺服系统进行纠偏，精度高。
刮平机构由中向外同步刮平，效率高，刮平效果好。
四点热熔定位，保证纠偏后传输过程不产生二次偏移。
能适用各种类型偏差，且纠偏尺寸范围大。



Functionality

Through vision and servo system for deviation correction, high accuracy. The scraping mechanism from the middle to the outside synchronous scraping, high efficiency, scraping effect is good. Four-point hot melt positioning to ensure that the transmission process does not produce secondary offset after correction. Can be applied to various types of deviation, and the correction size range is large.



技术参数 Specifications

项目 Item	数值 Value
纠偏精度 Correction accuracy	±1mm
节拍 Cycle time	≤15s
适用版型 Compatible module size	长 length: 1650-2550(mm); 宽width: 990-1450(mm)
电源 Power requirement	AC380V±5%, 3P+1N+1PE, 32A, 50/60Hz
功率 Power	4.5kW
工作气压 Air pressure	0.5-0.8(MPa)
噪音 Noise	≤70dB
外形尺寸 Dimension(L×W×H)	3530*1920*1885(mm)
重量 Weight	约2000kg